


Vol-1193

urn:nbn:de:0074-1193-9

Copyright © 2014 for the individual papers by the papers' authors. Copying permitted only for private and academic purposes. This volume is published and copyrighted by its editors.



DL 2014

**27th International Workshop
on Description Logics**

**Informal Proceedings of the 27th International Workshop on
Description Logics**

Vienna, Austria, July 17-20, 2014.

Edited by

Meghyn Bienvenu *

Magdalena Ortiz **

Riccardo Rosati ***

Mantas Simkus **

* Laboratoire de Recherche en Informatique, CNRS and University of Paris-Sud, France

** Institute of Information Systems, Vienna University of Technology, Austria

*** Dipartimento di Ingegneria Informatica, Automatica e Gestionale, Sapienza University of Rome, Italy

Table of Contents

- Preface and Conference Organisation

Invited Talks

- New Perspectives on Query Reformulation 1
Michael Benedikt
- Fragments of Logic, Language, and Computation 2
Patrick Blackburn
- Structured Data on the Web (or, a Personal Journey Away From and Back To Ontologies) 3
Alon Halevy

Oral Presentations

- Planning Problems for Graph Structured Data in Description Logics 4-7
Shqiponja Ahmetaj, Diego Calvanese, Magdalena Ortiz, Mantas Simkus
- SPARQL Update for Materialized Triple Stores under DL-Lite_RDFS Entailment 8-20
Albin Ahmeti, Diego Calvanese, Axel Polleres
- Temporal OBDA with LTL and DL-Lite 21-32
Alessandro Artale, Roman Kontchakov, Alisa Kovtunova, Vladislav Ryzhikov, Frank Wolter, Michael Zakharyashev
- Matching with Respect to General Concept Inclusions in the Description Logic EL 33-44
Franz Baader, Barbara Morawska
- Succinctness of Query Rewriting in OWL 2 QL: The Case of Tree-like Queries 45-57
Meghyn Bienvenu, Stanislav Kikot, Vladimir Podolskii
- Fuzzy DLs over Finite Lattices with Nominals 58-70
Stefan Borgwardt
- Gödel FL₀ with Greatest Fixed-Point Semantics 71-82
Stefan Borgwardt, José A. Leyva Galano, Rafael Peñaloza
- Query Inseparability by Games 83-95
Elena Botoeva, Roman Kontchakov, Vladislav Ryzhikov, Frank Wolter, Michael Zakharyashev
- Querying Inconsistent Description Logic Knowledge Bases under Preferred Repair Semantics 96-99
Camille Bourgaux, Meghyn Bienvenu, François Goasdoué
- Acyclic Query Answering under Guarded Disjunctive Existential Rules and Consequences to DLs 100-111

Pierre Bourhis, Michael Morak, Andreas Pieris

- Contextualized Knowledge Repositories with Justifiable Exceptions
Loris Bozzato, Thomas Eiter, Luciano Serafini 112-123
- Shape and Content: Incorporating Domain Knowledge into Shape Analysis
Diego Calvanese, Tomer Kotek, Mantas Simkus, Helmut Veith, Florian Zuleger 124-127
- Is Your Ontology as Hard as You Think? Rewriting Ontologies into Simpler DLs
David Carral, Cristina Feier, Ana Armas Romero, Bernardo Cuenca-Grau, Pascal Hitzler, Ian Horrocks 128-140
- Controlled Query Evaluation over Lightweight Ontologies
Bernardo Cuenca Grau, Evgeny Kharlamov, Egor Kostylev, Dmitriy Zheleznyakov 141-152
- On Faceted Search over Knowledge Bases
Bernardo Cuenca Grau, Evgeny Kharlamov, Dmitriy Zheleznyakov, Marcelo Arenas, Sarunas Marciuska 153-156
- DeaLing with Ontologies using CODs
Chiara Del Vescovo, Rafael Peñaloza 157-168
- Towards Practical Deletion Repair of Inconsistent DL-programs
Thomas Eiter, Michael Fink, Daria Stepanova 169-180
- Lower and Upper Approximations for Depleting Modules of Description Logic Ontologies
William Gatens, Boris Konev, Frank Wolter 181-184
- Abstraction Refinement for Ontology Materialization
Birte Glimm, Yevgeny Kazakov, Thorsten Liebig, Trung-Kien Tran, Vincent Vialard 185-196
- Query Rewriting under EL TBoxes: Efficient Algorithms
Peter Hansen, Carsten Lutz, Inanc Seylan, Frank Wolter 197-208
- Datalog Rewriting Techniques for Non-Horn Ontologies
Mark Kaminski, Yavor Nenov, Bernardo Cuenca Grau 209-220
- Goal-Directed Tracing of Inferences in EL Ontologies
Yevgeny Kazakov, Pavel Klinov 221-232
- Complexity of Temporal Query Abduction in DL-Lite
Szymon Klarman, Thomas Meyer 233-244
- Forgetting and Uniform Interpolation for ALC-Ontologies with ABoxes
Patrick Koopmann, Renate A. Schmidt 245-257
- XPath for DL-Lite Ontologies
Egor V. Kostylev, Juan L. Reutter, Domagoj Vrgoc 258-269
- Complexities of Nominal Schemas
Markus Krötzsch, Sebastian Rudolph 270-273
- Brave and Cautious Reasoning in EL
Michel Ludwig, Rafael Peñaloza 274-286

- Detecting Conjunctive Query Differences between ELHr-Terminologies using Hypergraphs 287-298
Michel Ludwig, Dirk Walther
- Axiom Dependency Hypergraphs for Fast Atomic Decomposition of Ontologies 299-310
Francisco Martin-Recuerda, Dirk Walther
- Parallel OWL 2 RL Materialisation in Centralised, Main-Memory RDF Systems 311-323
Boris Motik, Yavor Nenov, Robert Piro, Ian Horrocks, Dan Olteanu
- Optimised Absorption for Expressive Description Logics 324-335
Andreas Steigmiller, Birte Glimm, Thorsten Liebig
- Hybrid Query Answering Over DL Ontologies 336-339
Giorgos Stoilos, Giorgos Stamou
- Pushing the CFDnc Envelope 340-351
David Toman, Grant Weddell
- Pay-as-you-go Ontology Query Answering Using a Datalog Reasoner 352-364
Yujiao Zhou, Yavor Nenov, Bernardo Cuenca Grau, Ian Horrocks

Poster Presentations

- Measuring Conceptual Similarity in Ontologies: How Bad is a Cheap Measure? 365-377
Tahani Alsubait, Bijan Parsia, Uli Sattler
- A MILP-based Decision Procedure for the (Fuzzy) Description Logic ALCB 378-390
Fernando Bobillo, Umberto Straccia
- Gödel Description Logics with General Models 391-403
Stefan Borgwardt, Felix Distel, Rafael Peñaloza
- How to Best Nest Regular Path Queries 404-415
Pierre Bourhis, Markus Krötzsch, Sebastian Rudolph
- Expressive Identification Constraints to Capture Functional Dependencies in Description Logics 416-420
Diego Calvanese, Wolfgang Fischl, Reinhard Pichler, Emanuel Sallinger, Mantas Simkus
- Complexity Sources in Fuzzy Description Logic 421-433
Marco Cerami, Umberto Straccia
- Obfuscation of Semantic Data: Restricting the Spread of Sensitive Information 434-446
Federico Cerutti, Geeth de Mel, Timothy Norman, Nir Oren, Artemis Parvizi, Paul Sullivan, Alice Toniolo
- Bayesian Description Logics 447-458
Ismail Ilkan Ceylan, Rafael Peñaloza

- An ABox Revision Algorithm for the Description Logic EL_{bot} 459-470
Liang Chang, Uli Sattler, Tianlong Gu
- Evaluation of Extraction Techniques for Ontology Excerpts 471-482
Jieying Chen, Michel Ludwig, Yue Ma, Dirk Walther
- Graphol: Ontology Representation through Diagrams 483-495
Marco Console, Domenico Lembo, Valerio Santarelli, Domenico Fabio Savo
- Reducing Global Consistency to Local Consistency in Ontology-based Data Access - Extended Abstract 496-499
Marco Console, Maurizio Lenzerini
- Comparing the Expressiveness of Description Logics 500-512
Ali Rezaei Divroodi
- Reasoning about Belief Uncertainty in DL Lite N bool 513-525
Ala Djedjai, Hassina Seridi, Tarek Khadir
- Mary, What's Like All Cats? 526-529
Andreas Ecke, Rafael Peñaloza, Anni-Yasmin Turhan
- Generating Comprehensible Explanations in Description Logic 530-542
Fredrik Engström, Abdul Rahim Nizamani, Claes Strannegård
- Rational Closure in SHIQ 543-555
Laura Giordano, Valentina Gliozzi, Nicola Olivetti, Gian Luca Pozzato
- TBox Abduction in ALC Using a DL Tableau 556-566
Ken Halland, Arina Britz, Szymon Klarman
- Typed Higher-Order Variant of SROIQ - Why Not? 567-578
Martin Homola, Jan Kluka, Vojtěch Svátek, Miroslav Vacura
- Bridging the Gap between Tableau and Consequence-Based Reasoning 579-590
Yevgeny Kazakov, Pavel Klinov
- Towards a Description Logic for Program Analysis: Extending ALCQIO with Reachability 591-594
Tomer Kotek, Mantas Simkus, Helmut Veith, Florian Zuleger
- Visualization and Management of Mappings in Ontology-based Data Access (Progress Report) 595-607
Domenico Lembo, Riccardo Rosati, Marco Ruzzi, Domenico Fabio Savo, Emanuele Tocci
- Practical Query Answering over Hi (DL-LiteR) Knowledge Bases 608-619
Maurizio Lenzerini, Lorenzo Lepore, Antonella Poggi
- Temporalising EL Concepts with Time Intervals 620-632
Jared Leo, Ulrike Sattler, Bijan Parsia
- Towards Parallel Repair: An Ontology Decomposition-based Approach 633-645
Yue Ma, Rafael Peñaloza
- A Method to Develop Description Logic Ontologies Iteratively with Automatic Requirement Traceability 646-658

Yuri Malheiros, Fred Freitas

- An Empirical Investigation of Difficulty of Subsets of Description Logic Ontologies 659-670
Nicolas Matentzoglou, Bijan Parsia, Uli Sattler
- DIP: A Defeasible-Inference Platform for OWL Ontologies 671-683
Kody Moodley, Thomas Meyer, Uli Sattler
- Transition Constraints for Temporal Attributes 684-695
E. A. Nasubo Ongoma, C. Maria Keet, Thomas Meyer
- A Stream-Temporal Query Language for Ontology Based Data Access 696-708
Özgür Lütfü Özcep, Ralf Möller, Christian Neuenstadt
- Certain Answers in a Rough World 709-712
Rafael Peñaloza, Veronika Thost, Anni-Yasmin Turhan
- Predicting OWL Reasoners: Locally or Globally? 713-724
Viachaslau Sazonau, Uli Sattler, Gavin Brown
- OptiqueVQS: Visual Query Formulation for OBDA 725-728
Ahmet Soylu, Evgeny Kharlamov, Dmitriy Zheleznyakov, Ernesto Jimenez-Ruiz, Martin Giese, Ian Horrocks
- OBDA Using RL Reasoners and Repairing 729-733
Giorgos Stoilos
- Instance-driven TBox Revision in DL-Lite 734-745
Zhe Wang, Kewen Wang, Guilin Qi, Zhiqiang Zhuang, Yuefeng Li
- Rational Elimination of DL-Lite TBox Axioms 746-756
Zhiqiang Zhuang, Zhe Wang, Kewen Wang, Grigoris Antoniou

2014-07-09: submitted by Meghyn Bienvenu, Mantas Simkus

2014-07-10: published on CEUR-WS.org [valid HTML5]

Preface

The International Workshop on Description Logics is the main annual event of the description logic research community. It is devoted to discussing developments and applications of knowledge representation formalisms and systems based on description logics. The workshop explicitly welcomes submissions from researchers that are new to the area and provides quality feedback via peer reviewing, while at the same time being of an inclusive nature with a very high acceptance rate. There are only informal (electronic) proceedings and “publication” at the workshop is not supposed to preclude publication at conferences. More information, as well as the list of the previous editions of the workshop, can be found at <http://dl.kr.org>.

The 27th edition of the International Workshop on Description Logics was held in Vienna, Austria, on July 17–20, 2014, as part of the Vienna Summer of Logic. This year, a total of 80 papers were submitted, involving authors from 24 countries. Each submission was reviewed by at least three members of the program committee, or additional reviewers recruited by the PC members. A total of 34 papers were selected for oral presentation, and 36 papers were selected for poster presentation.

As in recent years, a Distinguished Student Paper Award was presented to the authors of a student paper, i.e., a paper that was authored independently by researchers who have not received a doctoral degree yet. This year’s award went to Stefan Borgwardt for his paper “Fuzzy DLs over Finite Lattices with Nominals” which contributes to our understanding of the complexity of reasoning in fuzzy description logics.

In addition to the presentation of the accepted papers, posters, and demos, the program featured three invited talks, which were given by Michael Benedikt, Patrick Blackburn, and Alon Y. Halevy. The abstracts of their talks are included in this volume. The talk by Patrick Blackburn was given as part of a joint session with the 15th International Workshop on Non-Monotonic Reasoning (NMR).

Our thanks go to all the authors, invited speakers, PC members, and additional reviewers who made the technical program possible. We’d also like to acknowledge the foundation for Principles of Knowledge Representation and Reasoning (KR Inc.) for financial support and EasyChair for providing a convenient and efficient platform for preparing the program. Last but not least, a warm thank you to all of the participants of DL 2014. We hope that attending the workshop has been an enjoyable and stimulating experience.

July 2014

Meghyn Bienvenu
Magdalena Ortiz
Riccardo Rosati
Mantas Simkus

A MILP-based decision procedure for the (Fuzzy) Description Logic \mathcal{ALCB}

Fernando Bobillo¹ and Umberto Straccia²

¹ Dpt. of Computer Science & Systems Engineering, University of Zaragoza, Spain

² Istituto di Scienza e Tecnologie dell'Informazione (ISTI - CNR), Pisa, Italy
Email: fbobillo@unizar.es, straccia@isti.cnr.it

Abstract. To overcome the inability of Description Logics (DLs) to represent vague or imprecise information, several fuzzy extensions have been proposed in the literature. In this context, an important family of reasoning algorithms for fuzzy DLs is based on a combination of tableau algorithms and Operational Research (OR) problems, specifically using Mixed Integer Linear Programming (MILP). In this paper, we present a MILP-based tableau procedure that allows to reason within fuzzy \mathcal{ALCB} , *i.e.*, \mathcal{ALC} with individual value restrictions. Interestingly, unlike classical tableau procedures, our tableau algorithm is deterministic, in the sense that it defers the inherent non-determinism in \mathcal{ALCB} to a MILP solver.

1 Introduction

Description Logics (DLs for short) [2] are a family of logics for representing structured knowledge. In the last two decades, DLs have gained even more popularity due to their application in the context of the *Semantic Web* [3]. Indeed, the current standard language for specifying ontologies is the Web Ontology Language (OWL 2) [18], which is based on the DL $\mathcal{SROIQ}(\mathbf{D})$ [23].

Fuzzy DLs have been proposed as an extension to classical DLs with the aim of dealing with *fuzzy/vague/imprecise concepts* by including elements of fuzzy logic [35]. In fuzzy DLs, the axioms may not be bivalent, but instead can be satisfied with a certain degree of truth (typically, a truth value in $[0, 1]$). Since the first work of J. Yen in 1991 [34], an important number of works can be found in the literature (good surveys on *fuzzy DLs* can be found on [25,33]).

Several families of algorithms to reason with fuzzy DLs have been proposed in the literature. The most important ones are tableau algorithms [15,28,29,30], tableau algorithms combined with Operational Research (OR) problems [8,17], automata-based algorithms [14,13], reduction to classical DLs [4,5,6,10,12], and reduction to fuzzy logics [16,19,22].

Some of the existing algorithms already support nominals. A tableau algorithm for Zadeh \mathcal{SHOIQ} [28] and an algorithm to check subsumption in Gödel \mathcal{EL}^{++} [26] are both able to deal with nominals. There are also reductions to classical DLs for fuzzy $\mathcal{SROIQ}(\mathbf{D})$ under Zadeh [4], finite Gödel [5], finite Łukasiewicz [10], and any finite t-norm [6]; but also for \mathcal{SHOI} for every t-norm not starting with the Łukasiewicz t-norm [12].

However, to the best of our knowledge, none of the existing OR-based tableau algorithms is able to support nominals so far. This family of algorithms is interesting for several reasons: *(i)* it is very suitable to manage fuzzy datatypes [31] or fuzzy concepts without a counterpart in classical DLs, such as fuzzy modified concepts [31] or aggregated concepts [11]; *(ii)* it makes it possible to reason with other t-norms different than Gödel [8]; and *(iii)* the arguably most popular fuzzy ontology reasoner `fuzzyDL` implements one of these algorithms [7].

The objective of this paper is to start filling this gap by proposing a novel decision procedure for a fuzzy DL with individual value restrictions, namely *ALCB*. *ALCB* is the basic DL language *ALC* [31] extended with individual value restrictions. Under the restriction that the TBox is acyclic, our algorithm applies for Lukasiewicz, Zadeh fuzzy DLs, and for classical DLs.

The rest of this paper is organised as follows. Section 2 includes some preliminary notions. Section 3 presents our reasoning algorithm and Section 4 a running example. Finally, Section 5 sets out some conclusions and ideas for future work.

2 Fuzzy DLs Basics

In this section we overview some basic definitions on mathematical fuzzy logic and the fuzzy DL *ALCB* (see [25,33] for a more in depth presentation).

Mathematical Fuzzy Logic. In *Mathematical Fuzzy Logic* [21], the usual convention prescribing that a statement is either true or false is changed and is a matter of degree measured on an ordered scale that is no longer $\{0, 1\}$, but e.g., $[0, 1]$. This degree is called *degree of truth* of the logical statement ϕ in the interpretation \mathcal{I} . For us, *fuzzy statements* have the form $\langle \phi, \alpha \rangle$, where $\alpha \in (0, 1]$ and ϕ is a statement, encoding that the degree of truth of ϕ is *greater than or equal to* α .

Fuzzy logics provide compositional calculi of degrees of truth. The conjunction, disjunction, complement and implication operations are performed in the fuzzy case by a t-norm function \otimes , a t-conorm function \oplus , a negation function \ominus and an implication function \Rightarrow , respectively (see [21] for definitions and properties of these functions). A quadruple composed by a t-norm, a t-conorm, an implication function and a negation function determines a *fuzzy logic*. One usually distinguishes three fuzzy logics, namely Lukasiewicz, Gödel, and Product [21], due to the fact that any continuous t-norm can be obtained as a combination of Lukasiewicz, Gödel, and Product t-norm [27]. It is also usual to consider also Zadeh logic. The combination functions of these logics can be found in Table 1.

It is easy to see that Zadeh fuzzy logic can be expressed using Lukasiewicz fuzzy logic, as $\min(\alpha, \beta) = \alpha \otimes_{\mathbf{L}} (\alpha \Rightarrow_{\mathbf{L}} \beta)$, $\max(\alpha, \beta) = 1 - \min(1 - \alpha, 1 - \beta)$, and $\alpha \Rightarrow_{KD} \beta = \max(1 - \alpha, \beta)$. This latter implication is called *Kleene-Dienes implication*. The name of Zadeh fuzzy logic is used following the tradition in the setting of fuzzy DLs, even if the name may lead to confusion because the logic does not usually include Rescher implication, sometimes called *Zadeh implication* as well. This implication is defined as $\alpha \Rightarrow \beta = 1$ if $\alpha \leq \beta$; 0 otherwise.

Table 1. Truth combination functions of various fuzzy logics.

	Lukasiewicz logic	Gödel logic	Product logic	Zadeh logic
$\alpha \otimes \beta$	$\max(\alpha + \beta - 1, 0)$	$\min(\alpha, \beta)$	$\alpha \cdot \beta$	$\min(\alpha, \beta)$
$\alpha \oplus \beta$	$\min(\alpha + \beta, 1)$	$\max(\alpha, \beta)$	$\alpha + \beta - \alpha \cdot \beta$	$\max(\alpha, \beta)$
$\alpha \Rightarrow \beta$	$\min(1 - \alpha + \beta, 1)$	$\begin{cases} 1 & \text{if } \alpha \leq \beta \\ \beta & \text{otherwise} \end{cases}$	$\min(1, \beta/\alpha)$	$\max(1 - \alpha, \beta)$
$\ominus \alpha$	$1 - \alpha$	$\begin{cases} 1 & \text{if } \alpha = 0 \\ 0 & \text{otherwise} \end{cases}$	$\begin{cases} 1 & \text{if } \alpha = 0 \\ 0 & \text{otherwise} \end{cases}$	$1 - \alpha$

The Fuzzy DL \mathcal{ALCB} . This logic is obtained by extending fuzzy \mathcal{ALC} with *individual value restrictions* (indicated with the letter \mathcal{B}). It is a sublogic of the fuzzy DL presented at [32]. Let \mathbf{A} be a set of *concept names* (also called atomic concepts), \mathbf{R} be a set of *role names*, and \mathbf{I} be a set of *individual names*. Each role $R \in \mathbf{R}$ is also called an *object property*. The set of *concepts* (denoted C, D) is built from concept names $A \in \mathbf{A}$ using connectives and quantification constructs over roles R and individuals $a \in \mathbf{I}$, according to the following syntactic rule:

$C, D \rightarrow$	A	(atomic concept)
	\top	(universal concept)
	\perp	(bottom concept)
	$\neg C$	(concept negation)
	$C \sqcap D$	(concept conjunction)
	$C \sqcup D$	(concept disjunction)
	$\forall R.C$	(universal restriction)
	$\exists R.C$	(existential restriction)
	$\exists R.\{a\}$	(<i>individual value restriction</i>) .

Now we will define the *axioms* that can be expressed in a fuzzy ontology. A fuzzy *knowledge base* or fuzzy ontology is a tuple $\mathcal{K} = \langle \mathcal{A}, \mathcal{T} \rangle$, where \mathcal{A} is an ABox with assertional axioms and \mathcal{T} is a TBox with terminological axioms. In the axioms, we will use $\alpha \in (0, 1]$ to denote a truth value. If α is omitted, $\alpha = 1$ is assumed.

An *ABox* \mathcal{A} (Assertional Box) is a finite set of concept assertions or role assertions. A *concept assertion* $\langle a:C, \alpha \rangle$ states that a is an instance of concept C to degree at least α . Furthermore, a *role assertion* $\langle (a_1, a_2):R, \alpha \rangle$ indicates that (a_1, a_2) is an instance of role R to degree at least α .

A *TBox* \mathcal{T} (Terminological Box) is a finite set of *General Concept Inclusion* (GCI) axioms of the form $\langle C \sqsubseteq D, \alpha \rangle$, indicating that C is a sub-concept of D to degree at least α . C is called the *head* and D is the *body* of the axiom. $C = D$ can be used as a shorthand for both $\langle C \sqsubseteq D, 1 \rangle$ and $\langle D \sqsubseteq C, 1 \rangle$. For a concept name A , we say that a *definitional axiom* is of the form $A = C$, while a *primitive inclusion axiom* is of the form $A \sqsubseteq C$. Furthermore, we say that A_1 *directly uses* A_2 w.r.t. \mathcal{T} if A_1 is the head of some axiom and A_2 occurs in its body. Let *uses* be the transitive closure of the relation directly uses. \mathcal{T} is *acyclic* if it has

primitive or definitional axioms only, a concept name A is the head of at most one definitional axiom in \mathcal{T} , there is no concept name A in the head of both a definitional and primitive inclusion axiom, and there is no concept name A such that A uses A .

Example 1. We have built a fuzzy wine ontology³ according to the FuzzyOWL 2 proposal [9]. Ontologies often use individual value restrictions to state geographical origins. For instance, the fuzzy wine ontology contains the following definition of Tuscan wines: $\text{TuscanWine} = \text{Wine} \sqcap \exists \text{locatedIn}.\{\text{TuscanyRegion}\}$.

Now, let us formally specify the semantics. Let us fix a fuzzy logic. In classical DLs, an interpretation \mathcal{I} maps e.g., a concept C into a set of individuals $C^{\mathcal{I}} \subseteq \Delta^{\mathcal{I}}$, *i.e.*, \mathcal{I} maps C into a function $C^{\mathcal{I}} : \Delta^{\mathcal{I}} \rightarrow \{0, 1\}$ (either an individual belongs to the extension of C or does not belong to it). However, in fuzzy DLs, \mathcal{I} maps C into a function $C^{\mathcal{I}} : \Delta^{\mathcal{I}} \rightarrow [0, 1]$ and, thus, an individual belongs to the extension of C to some degree in $[0, 1]$, *i.e.*, $C^{\mathcal{I}}$ is a fuzzy set. Specifically, a *fuzzy interpretation* is a pair $\mathcal{I} = (\Delta^{\mathcal{I}}, \cdot^{\mathcal{I}})$ consisting of a non-empty (crisp) set $\Delta^{\mathcal{I}}$ (the *domain*) and of a *fuzzy interpretation function* $\cdot^{\mathcal{I}}$ that assigns:

1. to each atomic concept A a function $A^{\mathcal{I}} : \Delta^{\mathcal{I}} \rightarrow [0, 1]$;
2. to each object property R a function $R^{\mathcal{I}} : \Delta^{\mathcal{I}} \times \Delta^{\mathcal{I}} \rightarrow [0, 1]$;
3. to each individual a an element $a^{\mathcal{I}} \in \Delta^{\mathcal{I}}$ such that $a^{\mathcal{I}} \neq b^{\mathcal{I}}$ if $a \neq b$ (called *Unique Name Assumption*, UNA). UNA is often not assumed in DLs.

Let $x, y \in \Delta^{\mathcal{I}}$ be elements of the domain. The fuzzy interpretation function is extended to complex concepts as follows:

$$\begin{aligned}
\top^{\mathcal{I}}(x) &= 1 \\
\perp^{\mathcal{I}}(x) &= 0 \\
(\neg C)^{\mathcal{I}}(x) &= \ominus C^{\mathcal{I}}(x) \\
(C \sqcap D)^{\mathcal{I}}(x) &= C^{\mathcal{I}}(x) \otimes D^{\mathcal{I}}(x) \\
(C \sqcup D)^{\mathcal{I}}(x) &= C^{\mathcal{I}}(x) \oplus D^{\mathcal{I}}(x) \\
(\forall R.C)^{\mathcal{I}}(x) &= \inf_{y \in \Delta^{\mathcal{I}}} \{R^{\mathcal{I}}(x, y) \Rightarrow C^{\mathcal{I}}(y)\} \\
(\exists R.C)^{\mathcal{I}}(x) &= \sup_{y \in \Delta^{\mathcal{I}}} \{R^{\mathcal{I}}(x, y) \otimes C^{\mathcal{I}}(y)\} \\
(\exists R.\{a\})^{\mathcal{I}}(x) &= R^{\mathcal{I}}(x, a^{\mathcal{I}}) \ .
\end{aligned}$$

The *satisfiability of axioms* is then defined by the following conditions:

1. \mathcal{I} satisfies $\langle a:C, \alpha \rangle$ if $C^{\mathcal{I}}(a^{\mathcal{I}}) \geq \alpha$;
2. \mathcal{I} satisfies $\langle (a, b):R, \alpha \rangle$ if $R^{\mathcal{I}}(a^{\mathcal{I}}, b^{\mathcal{I}}) \geq \alpha$;
3. \mathcal{I} satisfies $\langle C \sqsubseteq D, \alpha \rangle$ if $\inf_{x \in \Delta^{\mathcal{I}}} \{C^{\mathcal{I}}(x) \Rightarrow D^{\mathcal{I}}(x)\} \geq \alpha$.

Exceptionally, Zadeh fuzzy DLs use Zadeh implication in the semantics of GCIs, since Kleene-Dienes implication produce some counter-intuitive effects [4]. Note that classical \mathcal{ALCB} is a particular case of this fuzzy \mathcal{ALCB} . Finally, \mathcal{I} is a model of \mathcal{K} iff \mathcal{I} satisfies each axiom in \mathcal{K} .

³ <http://www.straccia.info/software/FuzzyOWL/ontologies/FuzzyWine.1.0.owl>

Reasoning tasks. Let \mathcal{K} be a fuzzy KB, C, D be fuzzy concepts, and α a degree of truth. We can define the following reasoning tasks:

- *Consistency.* \mathcal{K} is consistent iff it has a model, i.e., there is a fuzzy interpretation \mathcal{I} satisfying every axiom in \mathcal{K} .
- *Entailment:* \mathcal{K} entails an axiom $\langle \tau, \alpha \rangle$ iff every model of \mathcal{K} satisfies $\langle \tau, \alpha \rangle$.
- *Concept satisfiability.* C is satisfiable to at least degree α (or α -satisfiable) w.r.t. \mathcal{K} iff there is a model \mathcal{I} of \mathcal{K} such that $C^{\mathcal{I}}(x) \geq \alpha$ for some $x \in \Delta^{\mathcal{I}}$.
- *Concept subsumption.* D subsumes C to at least degree α (or α -subsumes) w.r.t. \mathcal{K} iff every model of \mathcal{K} satisfies the axiom $\langle C \sqsubseteq D, \alpha \rangle$.
- *Best entailment degree (BED).* The BED (also called greatest lower bound) of an axiom $\phi \in \{a:C, (a,b):R, C \sqsubseteq D\}$ w.r.t. \mathcal{K} is defined as $bed(\mathcal{K}, \phi) = \sup\{\alpha : \mathcal{K} \models \langle \phi, \alpha \rangle\}$, where $\sup \emptyset = 0$.

As usual in DLs and fuzzy DLs, reasoning tasks are often mutually inter-definable and each of the previous tasks can be reduced to the BED. For instance:

- \mathcal{K} is not consistent iff $bed(\mathcal{K}, a:\perp) = 1$, where a is new individual. Recall that inconsistent ontologies entail everything.
- \mathcal{K} entails $\langle \tau, \alpha \rangle$ iff $bed(\mathcal{K}, \tau) \geq \alpha$.
- C is α -satisfiable w.r.t. \mathcal{K} iff $\mathcal{K} \cup \{a:C, \alpha\}$ is consistent, where a is new individual. Note that consistency has already been reduced to the BED.
- D α -subsumes C w.r.t. \mathcal{K} iff $bed(\mathcal{K}, C \sqsubseteq D) \geq \alpha$.

3 A MILP-based Reasoning Algorithm for \mathcal{ALCB}

It has recently been shown that reasoning is undecidable for several fuzzy DLs in the presence of GCIs. This is the case *e.g.* in Lukasiewicz [17] and Product fuzzy DLs [1]. However, this is not the case in Zadeh DLs or in Lukasiewicz DLs with an acyclic TBox [17]. In the following, we will restrict to fuzzy KBs with acyclic TBoxes in classical, Zadeh and Lukasiewicz \mathcal{ALCB} . Note that it is enough to study the BED of a concept assertion since $bed(\mathcal{K}, (a,b):R) = bed(\mathcal{K}, a:\exists R.\{b\})$ and, in our case, $bed(\mathcal{K}, C \sqsubseteq D) = bed(\mathcal{K}, a : \neg C \sqcup D)$ for a new individual a .

Our algorithm starts by applying some tableau rules that decompose complex concept expressions into simpler ones but also generate a system of inequation constraints [31,33]. These inequations have to hold in order to respect the semantics of the DL constructors. After all rules have been applied, an optimisation problem must be solved before obtaining the final solution. This problem has a solution iff the fuzzy KB is consistent. In our case, we will end up with a bounded Mixed Integer Linear Programming [20] (MILP) problem, although in other fuzzy DLs Non Linear optimisation problems can be obtained. A MILP problem consists in minimizing a linear function with respect to a set of constraints that are linear inequations in which rational and integer variables can occur. In our case, MILP problems will be a *bounded* with rational variables ranging over $[0, 1]$ and integer variables ranging over $\{0, 1\}$.

We can assume without loss of generality that role assertions $\langle (a, b):R, \alpha \rangle$ are replaced by concept assertions $\langle a:\exists R.\{b\}, \alpha \rangle$, and that concepts are in *Negation Normal Form* (NNF), where the negation only appears before an atomic concept or an individual value restriction. In fact, a fuzzy concept $\neg C$ can be transformed into NNF by recursively applying these definitions: $\text{nnf}(\neg A) = \neg A$, $\text{nnf}(\neg \top) = \perp$, $\text{nnf}(\neg \perp) = \top$, $\text{nnf}(\neg \neg C) = C$, $\text{nnf}(\neg(C \sqcap D)) = \neg C \sqcup \neg D$, $\text{nnf}(\neg(C \sqcup D)) = \neg C \sqcap \neg D$, $\text{nnf}(\neg \forall R.C) = \exists R.\neg C$, $\text{nnf}(\neg \exists R.C) = \forall R.\neg C$, $\text{nnf}(\neg \exists R.\{a\}) = \neg \exists R.\{a\}$.

Algorithm 1 shows how to compute $\text{bed}(\mathcal{K}, a:C)$. Essentially, we consider an expression of the form $\langle a:\neg C, 1-x \rangle$, where x is a $[0, 1]$ -valued variable; this implies $(a:C)^x \leq x$. Then, we apply some satisfiability preserving tableau rules and *minimise* the original variable x such that all constraints are satisfied, that is, $\text{bed}(a:C, \mathcal{K}) := \inf x$ such that $\mathcal{K} \cup \{\langle a:\neg C, 1-x \rangle\}$ is consistent [7].

Our algorithm use *completion-forests* since an ABox might contain individuals with arbitrary roles connecting them. A completion-forest \mathcal{F} for \mathcal{K} is a collection of trees whose distinguished roots are arbitrarily connected by edges.

- Each node v is labeled with a set $\mathcal{L}(v)$ containing \mathcal{ALCB} concepts C or expressions of the forms $\{o\}$ and $\neg\{o\}$. If $C \in \mathcal{L}(v)$, we consider a variable $x_{v:C}$ meaning that v is an instance of C to degree greater than or equal to the value of the variable $x_{v:C}$. A novelty of this algorithm is the fact that if $\{o\} \in \mathcal{L}(v)$ then we consider a binary variable $x_{v:\{o\}}$. The intuition is that $x_{v:\{o\}} = 1$ iff v is interpreted as individual o . Similarly, if $\neg\{o\} \in \mathcal{L}(v)$ then we consider a binary variable $x_{v:\neg\{o\}}$ with the opposite meaning, *i.e.*, $x_{v:\neg\{o\}} = 1$ iff v is *not* interpreted as individual o .
- Each edge $\langle v, w \rangle$ is labeled with a set $\mathcal{L}(\langle v, w \rangle)$ of roles R and if $R \in \mathcal{L}(\langle v, w \rangle)$ then we consider a variable $x_{(v,w):R}$ representing the degree of being $\langle v, w \rangle$ and instance of R .

A node v containing some $\{a\} \in \mathcal{L}(v)$ is called a *nominal node*. Specifically, if $\{a\} \in \mathcal{L}(v)$ then v is called an a -nominal node. Note that for a nominal node v , $\mathcal{L}(v)$ may contain several $\{a_i\}$ and $\neg\{a_j\}$, for $1 \leq i, j \leq n$, where n is the number of individuals occurring in \mathcal{K} . For example we can have $\mathcal{L}(v) = \{\{a_1\}, \{a_2\}, \neg\{a_3\}, \neg\{a_4\}\}$. The notion of successor is needed when dealing with edges. A node w is an R -*successor* of node v if $R \in \mathcal{L}(\langle v, w \rangle)$.

We associate to the forest a set $\mathcal{C}_{\mathcal{F}}$ of constraints of the form $l \leq l'$, $l = l'$, $x_i \in [0, 1]$, $y_i \in \{0, 1\}$, where l, l' are linear expressions using the variables occurring in the forest. \mathcal{F} is then expanded by repeatedly applying the tableau rules in Table 2. Each rule instance is applied at most once, and the rules (N2), (N3) have the lowest priority. This means that they can only be applied when no other rule can be applied, right before solving the MILP problem, and hence the node v has to be one of the a_i .

Let us explain Algorithm 1. Firstly, Line 1 adds to the fuzzy KB the assertion $\langle a:\neg C, 1-x \rangle$, involving the variable x that will be minimized. Then, there is some preprocessing: lines 2-4 transform the concepts into NNF, lines 5-7 replace the role assertions with equivalent value restrictions, and lines 8-13 initialise the

forest from the axioms in the fuzzy KB by creating a nominal node for each individual. Then, Lines 14-17 apply the tableau rules until no other rule can be applied. Next, lines 18-27 introduce some additional constraints stating the range of each variable ($[0, 1]$ or $\{0, 1\}$). Finally, lines 28-33 return the minimised value of x if the optimisation problem has a solution; or a value 1 otherwise.

Algorithm 1 Computing $bed(a_0:C_0, \mathcal{K})$ in fuzzy \mathcal{ALCB} .

Input: A concept assertion $a_0:C_0$, a fuzzy KB \mathcal{K}

Output: BED of $a_0:C_0$ with respect to \mathcal{K}

```

1:  $\mathcal{K} \leftarrow \mathcal{K} \cup \{ \langle a_0 : \text{nnf}(\neg C_0), 1 - x \rangle \}$ 
2: for each concept assertion  $\langle a:C, \alpha \rangle \in \mathcal{K}$  do
3:    $\mathcal{K} \leftarrow (\mathcal{K} \setminus \{ \langle a:C, \alpha \rangle \}) \cup \{ \langle a : \text{nnf}(C), \alpha \rangle \}$ 
4: end for
5: for each role assertion  $\langle (a, b):R, \alpha \rangle \in \mathcal{K}$  do
6:    $\mathcal{K} \leftarrow (\mathcal{K} \setminus \{ \langle (a, b):R, \alpha \rangle \}) \cup \{ \langle a:\exists R.\{b\}, \alpha \rangle \}$ 
7: end for
8: create an empty forest  $\mathcal{F}$ 
9:  $\mathcal{C}_{\mathcal{F}} := \emptyset$ 
10: for each individual  $a$  occurring in  $\mathcal{K}$  do
11:   create a node  $v$ 
12:    $\mathcal{L}(v) := \mathcal{L}(v) \cup \{ \{a\} \}$ 
13: end for
14: repeat
15:   apply a rule in Table 2 to a node  $v$ 
16:   mark the applied rule as not applicable anymore to node  $v$ 
17: until no more rule can be applied to nodes in  $\mathcal{F}$ 
18: for each variable of the form  $x_v:C \in \mathcal{K}$  do
19:   if the logic is Łukasiewicz or Zadeh  $\mathcal{ALCB}$  then
20:      $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{ x_v:C \in [0, 1] \}$ 
21:   else
22:      $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{ x_v:C \in \{0, 1\} \}$ 
23:   end if
24: end for
25: for each variable  $z \in \mathcal{K}$  of the forms  $y, x_v:\{o\}, x_v:\neg\{o\}$  do
26:    $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{ z \in \{0, 1\} \}$ 
27: end for
28: if  $\mathcal{C}_{\mathcal{F}}$  has a solution then
29:   solve the optimisation problem on  $x$ 
30:   return  $x$ 
31: else
32:   return 1
33: end if

```

Table 2. Rules for fuzzy \mathcal{ALCB} with an acyclic TBox.

- (\top) IF $\top \in \mathcal{L}(v)$ THEN $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{x_{v:\top} = 1\}$.
- (\perp) IF $\perp \in \mathcal{L}(v)$ THEN $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{x_{v:\perp} = 0\}$.
- (\bar{A}) IF $\neg A \in \mathcal{L}(v)$ THEN
 1. $\mathcal{L}(v) = \mathcal{L}(v) \cup \{A\}$
 2. $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{x_{v:A} \leq 1 - x_{v:\neg A}\}$
- (\sqcap) IF $C_1 \sqcap C_2 \in \mathcal{L}(v)$ THEN
 1. $\mathcal{L}(v) = \mathcal{L}(v) \cup \{C_1, C_2\}$
 2. $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{x_{v:C_1} \otimes x_{v:C_2} \geq x_{v:C_1 \sqcap C_2}\}$
- (\sqcup) IF $C_1 \sqcup C_2 \in \mathcal{L}(v)$ THEN
 1. $\mathcal{L}(v) = \mathcal{L}(v) \cup \{C_1, C_2\}$
 2. $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{x_{v:C_1} \oplus x_{v:C_2} \geq x_{v:C_1 \sqcup C_2}\}$
- (\forall) IF $\forall R.C \in \mathcal{L}(v)$ AND w is an R -successor of v THEN
 1. $\mathcal{L}(w) = \mathcal{L}(w) \cup \{C\}$
 2. $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{x_{v:\forall R.C} \leq x_{(v,w):R} \Rightarrow x_{w:C}\}$
- (\exists) IF $\exists R.C \in \mathcal{L}(v)$ AND $C \neq \{a\}$ THEN
 1. create a new node w
 2. $\mathcal{L}(\langle v, w \rangle) = \mathcal{L}(\langle v, w \rangle) \cup \{R\}$
 3. $\mathcal{L}(w) = \mathcal{L}(w) \cup \{C\}$
 4. $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{x_{w:C} \otimes x_{(v,w):R} \geq x_{v:\exists R.C}\}$.
- (\sqsubseteq) IF $\langle A \sqsubseteq C, \alpha \rangle \in \mathcal{T}$ AND $A \in \mathcal{L}(v)$ THEN
 1. $\mathcal{L}(v) = \mathcal{L}(v) \cup \{C\}$
 2. $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{x_{v:A} \Rightarrow x_{v:C} \geq \alpha\}$
- ($=$) IF $A = C \in \mathcal{T}$ AND $A \in \mathcal{L}(v)$ THEN
 1. $\mathcal{L}(v) = \mathcal{L}(v) \cup \{C\}$
 2. $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{x_{v:A} = x_{v:C}\}$
- ($\neg =$) IF $A = C \in \mathcal{T}$ AND $\neg A \in \mathcal{L}(v)$ THEN
 1. $\mathcal{L}(v) = \mathcal{L}(v) \cup \{\neg C\}$
 2. $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{x_{v:\neg A} = x_{v:\neg C}\}$
- (Ass). IF $\langle a:C, \alpha \rangle \in \mathcal{K}$ AND v is an a -nominal node THEN
 1. $\mathcal{L}(v) = \mathcal{L}(v) \cup \{C\}$
 2. $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{x_{v:\{a\}} \Rightarrow x_{v:C} \geq \alpha\}$
- (\forall_o) IF $\neg \exists R.\{a\} \in \mathcal{L}(v)$ AND w is an R -successor of v THEN
 1. $\mathcal{L}(w) = \mathcal{L}(w) \cup \{\neg\{a\}\}$
 2. $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{x_{v:\neg \exists R.\{a\}} \leq x_{(v,w):R} \Rightarrow x_{w:\neg\{a\}}\}$.
- (\exists_o) IF $\exists R.\{a\} \in \mathcal{L}(v)$ AND w is an a -nominal node THEN
 1. $\mathcal{L}(\langle v, w \rangle) = \mathcal{L}(\langle v, w \rangle) \cup \{R\}$
 2. $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{x_{w:\{a\}} \Rightarrow (x_{v:\exists R.\{a\}} \Rightarrow x_{(v,w):R}) \geq 1\}$.
- (N1) IF $\neg\{a\} \in \mathcal{L}(v)$ THEN
 1. $\mathcal{L}(v) = \mathcal{L}(v) \cup \{\{a\}\}$
 2. $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{x_{v:\neg\{a\}} = 1 - x_{v:\{a\}}\}$.
- (N2) IF $\{\{a_1\}, \dots, \{a_n\}\} \subseteq \mathcal{L}(v)$ with $n \geq 2$ AND no other rule can be applied THEN $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{x_{v:\{a_1\}} + \dots + x_{v:\{a_n\}} \leq 1\}$.
- (N3) IF $\{a\} \in \mathcal{L}(v_i)$, for $1 \leq i \leq n$ AND no other rule can be applied THEN $\mathcal{C}_{\mathcal{F}} := \mathcal{C}_{\mathcal{F}} \cup \{x_{v_1:\{a\}} + \dots + x_{v_n:\{a\}} = 1\}$.

Now, let us explain the rationale behind the rules. Rules (\top) , (\perp) , (\bar{A}) , (\sqcap) , (\sqcup) , (\forall) , (\exists) , (\sqsubseteq) , $(=)$, and $(\neg =)$ have directly been derived from [17,31], so we do not comment them further.

According to the (Ass) rule, given an axiom $\langle a:C, \alpha \rangle$ and an a -nominal node v , we add C to $\mathcal{L}(v)$ and then add the constraint $x_{v:\{a\}} \Rightarrow x_{v:C} \geq \alpha$ to $\mathcal{C}_{\mathcal{F}}$. Since $x_{v:\{a\}}$ is binary, this is equivalent to say that either $x_{v:\{a\}} = 0$ or $x_{v:C} \geq \alpha$. That is, if v is interpreted as a , then v must belong to concept C with at least degree α . Notice that we apply the rule not only to the nominal nodes created during the initialisation phase, but also to all nominal nodes created during the inference process. (\forall_o) and (\exists_o) are similar to the rules managing universal restrictions and existential restrictions. Note that in the (\exists_o) rule, the equation $x_{w:\{a\}} \Rightarrow (x_{v:\exists R.\{a\}} \Rightarrow x_{(v,w):R}) \geq 1$ encodes the fact that if node w is interpreted as individual a then indeed the truth value of $x_{(v,w):R}$ has to be at least the truth value of $x_{v:\exists R.\{a\}}$.

(N1) avoids the inconsistency of having a node both interpreted and not interpreted as the same individual. (N2) deals with the UNA, and guarantees that a nominal node is not interpreted as more than one individual of the $a_i \in \mathcal{L}(v)$. Finally, (N3) makes sure that for every a -nominal node in the forest there is exactly one node interpreted as the individual a .

Concerning the MILP encoding of the fuzzy operators for classical, Łukasiewicz and Zadeh logics, we use the same ideas in *e.g.* [17,33]. Specifically, $x_1 \Rightarrow x_2 \geq z$ can be encoded as (denoted \mapsto) $\{1 - x_1 \oplus x_2 \geq z\}$. In Łukasiewicz, $x_1 \oplus x_2 \geq z \mapsto \{x_1 + x_2 \geq z\}$, while $x_1 \otimes x_2 \geq z \mapsto \{y \leq 1 - z, x_1 + x_2 - 1 \geq z - y, y \in \{0, 1\}\}$, where y is a new variable. In Zadeh, $x_1 \otimes x_2 \geq z \mapsto \{x_1 \geq z, x_2 \geq z\}$, while $x_1 \oplus x_2 \geq z \mapsto \{z \geq x_1, z \geq x_2, x_1 + y \geq z, x_2 + (1 - y) \geq z, y \in \{0, 1\}\}$, where y is a new variable. For classical DLs, any of the previous encodings is valid as long as we additionally force x_1, x_2 to be binary. It is convenient to chose those encodings that minimise the number of new variables.

Soundness, completeness, and termination can be proved similarly as in [17]:

Proposition 1. *Given a fuzzy KB \mathcal{K} in Łukasiewicz, Zadeh, and classical \mathcal{ALCB} with an acyclic $TBox$, Algorithm 1 terminates and correctly computes $bed(\mathcal{K}, a:C)$.*

4 A Running Example

Example 2. Consider the fuzzy KB $\mathcal{K} = \{b:A, c:B, a:\exists R.\{b\} \sqcup \exists R.\{c\}\}$ and let us show (the chosen fuzzy logic is irrelevant) that

$$bed(\mathcal{K}, a:\exists R.A \sqcup \exists R.\{c\}) = 1$$

The axioms of \mathcal{K} are already in NNF and there are no role assertions. Furthermore, to compute $bed(\mathcal{K}, a:\exists R.A \sqcup \exists R.\{c\})$, the axiom

$$\langle a:\forall R.\neg A \sqcap \neg \exists R.\{c\}, 1 - x \rangle \tag{1}$$

is added to \mathcal{K} . The forest initialisation creates three nodes v_1, v_2 , and v_3 being a b -nominal, c -nominal and a -nominal, respectively.

At first, the (Ass) rule is applied and, thus,

1. A is added to $\mathcal{L}(v_1)$;
2. B is added to $\mathcal{L}(v_2)$;
3. $\exists r.\{b\} \sqcup \exists r.\{c\}$ and $\forall R.\neg A \sqcap \neg \exists R.\{c\}$ are added to $\mathcal{L}(v_3)$;
4. $\mathcal{C}_{\mathcal{F}}$ contains so far expressions of the form $x_{v:\{a\}} \Rightarrow x_{v:C} \geq \alpha$, namely

$$\begin{aligned}
x_{v_1:\{b\}} &\Rightarrow x_{v_1:A} \geq 1 \\
x_{v_2:\{c\}} &\Rightarrow x_{v_2:B} \geq 1 \\
x_{v_3:\{a\}} &\Rightarrow x_{v_3:\exists R.\{b\} \sqcup \exists R.\{c\}} \geq 1 \\
x_{v_3:\{a\}} &\Rightarrow x_{v_3:\forall R.\neg A \sqcap \neg \exists R.\{c\}} \geq 1 - x .
\end{aligned}$$

Next, the (\sqcup) is applied to v_3 and, thus,

1. $\exists R.\{b\}$ and $\exists R.\{c\}$ are added to $\mathcal{L}(v_3)$;
2. $x_{v_3:\exists R.\{b\}} \oplus x_{v_3:\exists R.\{c\}} \geq x_{v_3:\exists R.\{b\} \sqcup \exists R.\{c\}}$ is added to $\mathcal{C}_{\mathcal{F}}$.

Then, the (\sqcap) rule is applied to v_3 and, thus,

1. $\forall R.\neg A$ and $\neg \exists R.\{c\}$ are added to $\mathcal{L}(v_3)$;
2. $x_{v_3:\forall R.\neg A} \otimes x_{v_3:\neg \exists R.\{c\}} \geq x_{v_3:\forall R.\neg A \sqcap \neg \exists R.\{c\}}$ is added to $\mathcal{C}_{\mathcal{F}}$.

Next, we apply the (\exists_o) rule to $\exists R.\{b\} \in \mathcal{L}(v_3)$ and, thus,

1. R is added to $\mathcal{L}(\langle v_3, v_1 \rangle)$;
2. $x_{v_1:\{b\}} \Rightarrow (x_{v_3:\exists R.\{b\}} \Rightarrow x_{(v_3, v_1):R}) \geq 1$ is added to $\mathcal{C}_{\mathcal{F}}$.

Now we can apply the (\forall) rule to $\mathcal{L}(v_3)$ and, thus,

1. $\neg A$ is added to $\mathcal{L}(v_1)$;
2. $x_{v_3:\forall R.\neg A} \leq x_{(v_3, v_1):R} \Rightarrow x_{v_1:\neg A}$ is added to $\mathcal{C}_{\mathcal{F}}$.

After that, we can apply the (\forall_o) rule to $\mathcal{L}(v_3)$ and, thus,

1. $\neg\{c\}$ is added to $\mathcal{L}(v_1)$;
2. $x_{v_3:\neg \exists R.\{c\}} \leq x_{(v_3, v_1):R} \Rightarrow x_{v_1:\neg\{c\}}$ is added to $\mathcal{C}_{\mathcal{F}}$.

Then, the $(N1)$ rule adds $\{c\}$ to $\mathcal{L}(v_1)$ and $x_{v_1:\neg\{c\}} = 1 - x_{v_1:\{c\}}$ to $\mathcal{C}_{\mathcal{F}}$. Since v_1 is also a c -nominal node now, we may apply the (Ass) rule to it, so

1. B is added to $\mathcal{L}(v_1)$;
2. $x_{v_1:\{c\}} \Rightarrow x_{v_1:B} \geq 1$ is added to $\mathcal{C}_{\mathcal{F}}$.

The (\exists_o) rule is applied next to $\exists R.\{c\} \in \mathcal{L}(v_3)$ and, thus,

1. R is added to $\mathcal{L}(\langle v_3, v_2 \rangle)$;
2. $x_{v_1:\{c\}} \Rightarrow (x_{v_3:\exists R.\{c\}} \Rightarrow x_{(v_3, v_1):R}) \geq 1$ is added to $\mathcal{C}_{\mathcal{F}}$;
3. $x_{v_2:\{c\}} \Rightarrow (x_{v_3:\exists R.\{c\}} \Rightarrow x_{(v_3, v_2):R}) \geq 1$ is added to $\mathcal{C}_{\mathcal{F}}$.

As now node v_2 has become an R -successor of v_3 , we may apply the (\forall) and (\forall_o) rules to $\mathcal{L}(v_3)$ and, thus,

1. $\neg A$ is added to $\mathcal{L}(v_2)$;
2. $x_{v_3:\forall R.\neg A} \leq x_{(v_3, v_2):R} \Rightarrow x_{v_2:\neg A}$ is added to $\mathcal{C}_{\mathcal{F}}$;

3. $\neg\{c\}$ is added to $\mathcal{L}(v_2)$;
4. $x_{v_3:\neg\exists R.\{a\}} \leq x_{(v_3,v_2):R} \Rightarrow x_{v_2:\neg\{c\}}$ is added to $\mathcal{C}_{\mathcal{F}}$.

The (N1) rule adds now adds $\{c\}$ to $\mathcal{L}(v_2)$ and $x_{v_2:\neg\{c\}} = 1 - x_{v_2:\{c\}}$ to $\mathcal{C}_{\mathcal{F}}$. Eventually, rule (N2) and (N3) add the following constraints to $\mathcal{C}_{\mathcal{F}}$:

1. $x_{v_1:\{b\}} + x_{v_1:\{c\}} \leq 1$;
2. $x_{v_3:\{a\}} = 1$;
3. $x_{v_1:\{b\}} = 1$;
4. $x_{v_1:\{c\}} + x_{v_2:\{c\}} = 1$.

Finally, we have to determine the minimal value of x such that $\mathcal{C}_{\mathcal{F}}$ is satisfiable. Therefore, from the last equations, we get immediately that $x_{v_1:\{b\}} = 1$, $x_{v_3:\{a\}} = 1$, $x_{v_1:\{c\}} = 0$, and $x_{v_2:\{c\}} = 1$. Of course, then $x_{v_2:\neg\{c\}} = 0$ and $x_{v_1:\neg A} = 0$. The assertion $a:\exists R.\{b\} \sqcup \exists R.\{c\}$ implies that $x_{v_3:\exists R.\{b\}} = 1$ or $x_{v_3:\exists R.\{c\}} = 1$. If $x_{v_3:\exists R.\{b\}} = 1$ then from $x_{v_1:\{b\}} \Rightarrow (x_{v_3:\exists R.\{b\}} \Rightarrow x_{(v_3,v_1):R}) \geq 1$ we get that $x_{(v_3,v_1):R} = 1$, while if $x_{v_3:\exists R.\{c\}} = 1$ from $x_{v_2:\{c\}} \Rightarrow (x_{v_3:\exists R.\{c\}} \Rightarrow x_{(v_3,v_2):R}) \geq 1$ we get that $x_{(v_3,v_2):R} = 1$. Now, suppose $x < 1$. From Equation 1, $x_{v_3:\forall R.\neg A \sqcap \neg \exists R.\{c\}} > 0$, and thus $x_{v_3:\forall R.\neg A} > 0$ and $x_{v_3:\neg \exists R.\{c\}} > 0$. If $x_{(v_3,v_1):R} = 1$, we get a contradiction with $x_{v_1:\neg A} = 0$, while if $x_{(v_3,v_2):R} = 1$, we get a contradiction with $x_{v_2:\neg\{c\}} = 0$. However, for $x = 1$ $\mathcal{C}_{\mathcal{F}}$ is satisfiable, so our algorithm returns $x = 1$. Indeed, $bed(\mathcal{K}, a:\exists R.A \sqcup \exists R.\{c\}) = 1$ holds.

5 Conclusions and Future Work

In this paper we have proposed the first algorithm based on OR to reason with fuzzy DLs including individual value restrictions. In particular, we have proposed an algorithm to compute the BED in classical, Zadeh, and Łukasiewicz \mathcal{ALCB} if the TBox is acyclic. The algorithm could be extended to the case of general TBoxes using blocking. A relevant property of the algorithm is that only one optimisation problem has to be solved, deferring the inherent non-determinism in \mathcal{ALCB} to the optimisation problem solver.

Future work will include the extension of the algorithm to more expressive fuzzy DLs, such as $\mathcal{SHLFB}(\mathbf{D})$. Up to know, $\mathcal{SHLFB}(\mathbf{D})$ is current the most expressive fuzzy DL for which there is an implementation of an OR-algorithm (the *fuzzyDL* system). On the one hand, adding inverse roles to the language seems challenging because of the possibility of having inverse functional role axioms. On the other hand, it would also be interesting to have unrestricted nominals to arbitrarily form complex concept expressions. Another possible extension is considering fuzzy nominals of the form $\{\alpha/o\}$ that can be used to describe fuzzy sets by enumeration of their elements [4].

Last but not least, we are aware that the current proposal is not optimal in the handling of nominal nodes, as several a -nominal nodes may occur in a completion-forest. We plan to adapt and implement the well-known *node merging* technique developed for classical DLs, such as for \mathcal{SHOIQ} [24], to the fuzzy case as well, analyse the overall computational complexity and experiment the algorithm within *fuzzyDL*.

References

1. F. Baader, S. Borgwardt, and R. Peñaloza. On the decidability status of fuzzy \mathcal{ALC} with general concept inclusions. *Journal of Philosophical Logic*, In press.
2. F. Baader, D. Calvanese, D. McGuinness, D. Nardi, and P. F. Patel-Schneider, editors. *The Description Logic Handbook: Theory, Implementation, and Applications*. Cambridge University Press, 2003.
3. T. Berners-Lee, J. Hendler, and O. Lassila. The semantic web. *The Scientific American*, 284(5):34–43, 2001.
4. F. Bobillo, M. Delgado, and J. Gómez-Romero. Crisp representations and reasoning for fuzzy ontologies. *International Journal of Uncertainty, Fuzziness and Knowledge-Based Systems*, 17(4):501–530, 2009.
5. F. Bobillo, M. Delgado, J. Gómez-Romero, and U. Straccia. Fuzzy description logics under Gödel semantics. *International Journal of Approximate Reasoning*, 50(3):494–514, 2009.
6. F. Bobillo, M. Delgado, J. Gómez-Romero, and U. Straccia. Joining Gödel and Zadeh fuzzy logics in fuzzy description logics. *International Journal of Uncertainty, Fuzziness and Knowledge-Based Systems*, 20:475–508, 2012.
7. F. Bobillo and U. Straccia. fuzzyDL: An expressive fuzzy description logic reasoner. In *Proceedings of the 17th IEEE International Conference on Fuzzy Systems (FUZZ-IEEE 2008)*, pages 923–930, June 2008.
8. F. Bobillo and U. Straccia. Fuzzy description logics with general t-norms and datatypes. *Fuzzy Sets and Systems*, 160(23):3382–3402, 2009.
9. F. Bobillo and U. Straccia. Fuzzy ontology representation using OWL 2. *International Journal of Approximate Reasoning*, 52:1073–1094, 2011.
10. F. Bobillo and U. Straccia. Reasoning with the Łukasiewicz fuzzy description logic *SRIOQ*. *Information Sciences*, 181:758–778, 2011.
11. F. Bobillo and U. Straccia. Aggregation operators for fuzzy ontologies. *Applied Soft Computing*, 13:3816–3830, 2013.
12. S. Borgwardt, F. Distel, and R. Peñaloza. How fuzzy is my fuzzy description logic? In B. Gramlich, D. Miller, and U. Sattler, editors, *Proceedings of the 6th International Joint Conference on Approximate Reasoning (IJCAR 2012)*, volume 7364 of *Lecture Notes in Artificial Intelligence*, pages 82–96. Springer-Verlag, 2012.
13. S. Borgwardt, F. Distel, and R. Peñaloza. Decidable Gödel description logics without the finitely-valued model property. In *Proceedings of the 14th International Conference on Principles of Knowledge Representation and Reasoning (KR 2014)*. AAAI Press, 2014.
14. S. Borgwardt and R. Peñaloza. The complexity of lattice-based fuzzy description logics. *Journal on Data Semantics*, 2(1):1–19, 2013.
15. S. Borgwardt and R. Peñaloza. Consistency reasoning in lattice-based fuzzy description logics. *International Journal of Approximate Reasoning*, In press.
16. M. Cerami, A. García-Cerdaña, and F. Esteva. On finitely-valued fuzzy description logics. *International Journal of Approximate Reasoning*, In press.
17. M. Cerami and U. Straccia. On the (un)decidability of fuzzy Description Logics under Łukasiewicz t -norm. *Information Sciences*, 227:1–21, 2013.
18. B. Cuenca-Grau, I. Horrocks, B. Motik, B. Parsia, P. F. Patel-Schneider, and U. Sattler. OWL 2: The next step for OWL. *Journal of Web Semantics*, 6(4):309–322, 2008.
19. A. García-Cerdaña, E. Armengol, and F. Esteva. Fuzzy Description Logics and t -norm based fuzzy logics. *International Journal of Approximate Reasoning*, 51(6):632–655, 2010.

20. M. K. H. Salkin. *Foundations of Integer Programming*. North-Holland, 1988.
21. P. Hájek. *Metamathematics of Fuzzy Logic*. Kluwer, 1998.
22. P. Hájek. Making fuzzy description logic more general. *Fuzzy Sets and Systems*, 154(1):1–15, 2005.
23. I. Horrocks, O. Kutz, and U. Sattler. The even more irresistible *SHOIQ*. In *Proceedings of the 10th International Conference on Principles of Knowledge Representation and Reasoning (KR 2006)*, pages 57–67. AAAI Press, 2006.
24. I. Horrocks and U. Sattler. A tableau decision procedure for *SHOIQ*. *Journal of Automated Reasoning*, 39(3):249–276, 2007.
25. T. Lukasiewicz and U. Straccia. Managing uncertainty and vagueness in description logics for the semantic web. *Journal of Web Semantics*, 6:291–308, 2008.
26. T. P. Mailis, G. Stoilos, N. Simou, G. B. Stamou, and S. D. Kollias. Tractable reasoning with vague knowledge using fuzzy \mathcal{EL}^{++} . *Journal of Intelligent Information Systems*, 39:399–440, 2012.
27. P. S. Mostert and A. L. Shields. On the structure of semigroups on a compact manifold with boundary. *Annals of Mathematics*, 65(1):117–143, 1957.
28. G. Stoilos and G. Stamou. Reasoning with fuzzy extensions of OWL and OWL 2. *Knowledge and Information Systems*, In press.
29. G. Stoilos, G. Stamou, J. Z. Pan, V. Tzouvaras, and I. Horrocks. Reasoning with very expressive fuzzy description logics. *Journal of Artificial Intelligence Research*, 30(8):273–320, 2007.
30. U. Straccia. Reasoning within fuzzy description logics. *Journal of Artificial Intelligence Research*, 14:137–166, 2001.
31. U. Straccia. Description logics with fuzzy concrete domains. In *Proceedings of the 21st Conference on Uncertainty in Artificial Intelligence (UAI 2005)*, pages 559–567. AUAI Press, 2005.
32. U. Straccia. A fuzzy description logic for the semantic web. In E. Sanchez, editor, *Fuzzy Logic and the Semantic Web*, Capturing Intelligence, chapter 4, pages 73–90. Elsevier, 2006.
33. U. Straccia. *Foundations of Fuzzy Logic and Semantic Web Languages*. CRC Studies in Informatics Series. Chapman & Hall, 2013.
34. J. Yen. Generalizing term subsumption languages to fuzzy logic. In *Proceedings of the 12th International Joint Conference on Artificial Intelligence (IJCAI 1991)*, pages 472–477, Sydney, Australia, 1991.
35. L. A. Zadeh. Fuzzy sets. *Information and Control*, 8(3):338–353, 1965.